

ARE YOU "READY TO RACE"?



The motorcycles advertised in this folder are only suitable for use in normal traffic in the homologated (restricted) version.

When purchasing a motorcycle, it is necessary to clearly observe all safety aspects and appropriate warnings. The motorcycles illustrated are in part equipped with extras that are subject to additional costs. All information concerning delivery, appearance, performance and weights and measurements of the vehicles comply with KTM's sales program in Austria at the time of printing and all information is supplied without obligation and may be subject to alteration at any time. Please note that model specifications can be different from country to country.

LEGAL DISCLAIMER

Should not be emulated.

The riders illustrated are professional motorcycle riders. Photos were taken on a closed racing circuit. KTM draws to the attention of all motorcycle riders that they should abide by all traffic laws and regulations, that they should wear the recommended protective clothing and always ride in a responsible way.

» www.ktm.com

| 990 SUPER DUKE R | | |
|------------------------------|--|--|
| ENGINE | 2-cylinder, 4-stroke, V 75° | |
| DISPLACEMENT | 999 cc | |
| BORE X STROKE | 101/62.4 mm | |
| PERFORMANCE | 88 kW @ 9,000 U/min | |
| MAX. TORQUE | 100 Nm @ 7,000 U/min | |
| COMPRESSION RATIO | 11.5:1 | |
| STARTER | E-Starter | |
| TRANSMISSION | 6 gears, claw-shift | |
| FUEL MIXTURE GENERATION | Electronic fuel injection | |
| CONTROL | 4-valve/DOHC | |
| LUBRICATION | Forced oil lubrication | |
| ENGINE LUBRICATION | Motorex Power Synt 4T 10W - 50 | |
| PRIMARY DRIVE | 67:35 | |
| FINAL DRIVE | 16:38 | |
| COOLING | Liquid cooled | |
| CLUTCH | Multi-disc wet clutch, hydraulically operated | |
| MOTOR MANAGEMENT | Keihin EMS | |
| CHASSIS | | |
| FRAME | Chromium-Molybdenum tubular frame, powder-coated | |
| SUBFRAME | Aluminium | |
| HANDLEBAR | Renthal Aluminium, tapered | |
| FRONT SUSPENSION | WP-USD Ø 48 mm | |
| REAR SUSPENSION | WP-Monoshock | |
| SUSPENSION TRAVEL FRONT/REAR | 135/150 mm | |
| FRONT BRAKE | 2 x Brembo 4-piston fixed caliper, 2 x brake discs Ø 320 mm | |
| REAR BRAKE | Brembo single-piston floating caliper, brake disc Ø 240 mm | |
| RIMS FRONT/REAR | 3.5 x 17"; 5.5 x 17" | |
| TYRES FRONT/REAR | 120/70 ZR 17"; 180/55 ZR 17" | |
| CHAIN | X-Ring chain 5/8 x 5/16" | |
| BATTERY | 12 V/11.2 Ah | |
| SILENCER | Stainless steel with catalytic converter | |
| STEERING HEAD ANGLE | 67.3° | |
| TRAIL | 93.9 mm | |
| WHEEL BASE | 1,450 mm | |
| GROUND CLEARANCE (UNLOADED) | 140 mm | |
| SEAT HEIGHT | 865 mm | |
| TANK CAPACITY | approx. 18.5 litre | |
| WEIGHT (READY TO RACE) | approx. 186 kg (no fuel) | |



KTM POWERWEAR

KTM POWERPARTS

KTM ADVENTURE TOURS



KTM-Sportmotorcycle AG
5230 Mattighofen/Austria
www.ktm.com